

10/18/00

10-18-00
19

A

Case Docket No. 00-631

THE COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of:

INVENTOR: Takashi Yamaguchi et al.

FOR: NUMBER DRAWINGS APPARATUS AND GAME MACHINE THEREWITH

Enclosed are:

- (XXXXXX) Seven sheets of drawings.
- () An Assignment of the invention to _____.
- () A certified copy of _____ Application No. _____, Filed _____.
- () Verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27.
- (XXXXXX) Preliminary Amendment.

The filing fee has been calculated as shown below:


			SMALL ENTITY		OTHER THAN A SMALL ENTITY	
For	No. Filed	No. Extra	Rate	Fee	Rate	Fee
Basic Fee				\$ 355		\$ 710
Total Claims	22	-20 = 2	x 9	\$	x 18	\$ 36
Indep Claims	6	-3 = 3	x 39	\$	x 78	\$ 234
Multiple Dependent Claim () Presented			+130	\$	+260	\$
			TOTAL	\$	TOTAL	\$ 980

- () Please charge my Deposit Account No. 02-0184 in the amount of \$ _____. A duplicate copy of this sheet is enclosed.
- (XX) A check in the amount of \$980.00 to cover the filing fee is enclosed.
- (XX) The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 02-0184. A duplicate copy of this sheet is enclosed.
 - (X) Any additional filing fees required under 37 CFR 1.16.
 - (X) Any patent application processing fees under 37 CFR 1.17.
- (XX) The Commissioner of hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 02-0184. A duplicate copy of this sheet is enclosed.
 - (X) Any patent application processing fees under 37 CFR 1.17.
 - (X) Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Date: October 18, 2000

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail in an envelope addressed to: Commissioner of Patents and Trademarks, Washington, D.C. 20231

October 18, 2000
(Date of Deposit)
Rachel Piscitelli
Name and Reg. No. of Attorney
Signature
October 18, 2000
Date of Signature


Gregory P. LaPointe
Attorney for Applicants
Bachman & LaPointe, P.C.
Suite 1201-900 Chapel Street
New Haven, CT 06510-2802
Telephone: (203) 777-6628

Express Mail No. EL398544594US

1c682 U.S. PTO
09/691435
10/18/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Takashi Yamaguchi et al. Docket No.: 00-631
Serial No.: Examiner :
Filed : Art Unit :
For : NUMBER DRAWINGS APPARATUS AND GAME MACHINE THEREWITH

Suite 1201
900 Chapel Street
New Haven, CT 06510-2802

PRELIMINARY AMENDMENT

Hon. Commissioner of Patents & Trademarks
United States Patent & Trademark Office
Washington, D.C. 20231

Dear Sir:

In the above-identified application for United States patent,
please amend as follows.

IN THE CLAIMS

Please amend the claims as follows.

Claim 13, lines 1 and 2 delete "one of Claims 1 to 12," and
substitute therefor --Claim 1,--.

Claim 15, lines 1 and 2 delete "one of Claims 1, 5, and 14," and
substitute therefor --Claim 1,--.

Claim 16, lines 1 and 2 delete "one of Claims 1 to 12, and 14,"
and substitute therefor --Claim 1,--.

Claim 22, line 1 delete "one of claims 19 to 21," and substitute
therefor --Claim 19,--.

REMARKS

Amendments have been made to the claims to remove the multiple dependencies in order to conform with U.S. practice. An early action on the merits is respectfully requested.

If any fees are required in connection with this case, it is respectfully requested that they be charged to Deposit Account No. 02-0184.

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail in an envelope addressed to Commissioner of Patents and Trademarks, Washington, D.C. 20231

on October 18, 2000
(Date of Deposit)

Rachel Piscitelli
Name and Reg. No. of Attorney

Rachel Piscitelli
Signature

October 18, 2000
Date of Signature

Respectfully submitted,

Takashi Yamaguchi et al.

By

Gregory F. LaPointe
Attorney for Applicant
Telephone - (203) 777-6628

Date: October 18, 2000

Express Mail No.:
EL398544594US

Express Mail No.:
EL398544594USon October 18, 2000(Date of Deposit)
Rachel PiscitelliRachel Piscitelli
(Signature)
October 18, 2000
(Date)

- 1 -

WFA-093-US

NUMBER DRAWING APPARATUS AND GAME MACHINE THEREWITH

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a number drawing apparatus that provides a fair draw of numbers for entertainment purposes using rolling bodies such as spheres (balls), and relates to a game machine provided with the number drawing apparatus.

2. Description of the Related Art

In games such as bingo, a player is often blindfolded and allowed to pick some balls from among a plurality of balls so as to be excited with anticipation.

There are bingo game machines that automatically perform the selection operation. For example, Japanese Unexamined Patent Application Publication No. 6-71010 discloses a bingo game machine (herein, termed the first well-known art) including a spherical rotating basket, which rotates to mix a plurality of balls in the basket, and a ball catcher provided in the rotating basket; each ball bears a symbol, and when a ball from among the mixed up balls falls into the ball catcher, the symbol thereon is read.

There is also a bingo game machine (herein, termed the second well-known art) including a rotating dish that slowly rotates on a center axis at the concave central portion and a plurality of marked ball catchers

003/033-1000

- 2 -

provided on the rotating dish, in which a plurality of balls, rolled onto the rotating disk by some technique, fall into some of the ball catchers, and symbols corresponding to the ball catchers are used for bingo.

In the first well-known art, the mechanism for rotating the basket for mixing the balls is complex, which increases the total cost of the game machine. Since the game machine allows the player to select one ball from among the mixed balls and leads the selected ball to a detecting unit to detect its unique identification, an identifying symbol must be provided on each of the balls, and this increases the cost of the balls. In addition, all the mixed balls must be caught by the ball catchers, so that the total time required for one game may be prolonged.

In the second well-known art, the added cost of the balls, which is a problem in the first well-known art, is eliminated because the selected symbol is instead specified by a corresponding ball catcher on the rotating dish. Nevertheless, the cost of the rotating dish itself is higher due to the division of the dish in order to satisfy the need to provide the rotating dish with ball-catching holes including sensors. When the balls move outwardly or fall into the center, there may be a case where the time required for one game is prolonged because the user must put balls back into the game machine.

In both the first well-known art and the second well-known art, the fairness of the bingo is emphasized, and it is not intended that the movement of the balls themselves be enjoyed by the players.

SUMMARY OF THE INVENTION

- 3 -

Accordingly, it is an object of the present invention to provide a number drawing apparatus in which time management is improved and which is very entertaining, and to provide a game machine provided with the number drawing apparatus.

It is another object of the present invention to provide a game machine including the above-described number drawing apparatus, which provides a player with a game prize in accordance with the result of the draw by the above number drawing apparatus.

To these ends, according to an aspect of the present invention, the above objects are achieved through provision of a number drawing apparatus including a rotating unit having a surface which rolls rolling bodies supplied thereon, and a driving unit for rotating the rotating unit in a fixed plane so that the supplied rolling bodies move outwardly. Information specified by the outward movement of each of the supplied rolling bodies is used as the result of the draw.

Preferably, unique information specified by the moving rolling bodies when the bodies have stopped is used as the result of the draw.

A plurality of regions to which unique symbols are assigned may be provided along the periphery of the rotating unit, and the result of the draw may be determined by the symbols assigned to the regions in which the rolling bodies stops.

According to another aspect of the present invention, the above objects are achieved through provision of a number drawing apparatus including a rotating unit having a surface which rolls rolling bodies supplied to the surface, a rolling-body supply unit for supplying the

003407 547660

- 4 -

rolling bodies from the central portion of the rotating unit to the surface, a driving unit for rotating the rotating unit in a fixed plane so that each of the supplied rolling bodies randomly travels outwardly from a supplied position in a direction toward the periphery of the rotating unit, and a plurality of catching units provided along the periphery of the rotating unit, the catching units each having a unique symbol assigned thereto. The result of the draw is specified by the symbol assigned to the catching unit in which the moving rotating body having flown out is caught.

Preferably, the plurality of catching units each include a detecting means for outputting a predetermined signal when the rolling body is caught, and the output signal specifies the symbol assigned to the catching unit in which the rolling body is caught.

When the catching units catch the rolling bodies, the catching units may hold the rolling bodies so that the rolling bodies partly protrude, and may allow the rolling bodies to fall with predetermined timing.

Until N different symbols are determined in sets of N rolling bodies where N represents a natural number not less than 2, the catching units may hold the N rolling bodies, and may allow all the N rolling bodies to simultaneously fall with predetermined timing.

The rolling-body-supply means may include a supply hole for supplying the rolling bodies, and a guidance mechanism for accelerating the rolling bodies and for guiding the accelerated rolling bodies to the surface.

Preferably, the distance between the supply hole and the surface is equal in all directions.

003101 5416560

- 5 -

The number drawing apparatus may further include a return wall for returning each of the rolling bodies which has not been caught by any one of the catching units.

Preferably, the return wall accelerates the rolling body and returns the accelerated rolling body.

The rolling bodies may be spheres.

According to another aspect of the present invention, the above objects are achieved through the provision of a number drawing apparatus including a rotating unit having a surface which rolls rolling bodies in which each attitude of the rolling bodies or each position at which the rolling bodies stop specifies a unique symbol, a rolling-body supply unit for supplying the rolling bodies from the central portion of the rotating unit to the surface, and a driving unit for rotating the rotating unit so that each of the supplied rolling bodies randomly moves outwardly from a supplied position in a direction toward the periphery of the rotating unit. Symbols specified by the rolling bodies when the rolling bodies have stopped are used as the results of the draw.

Preferably, the game machine is a bingo game machine in which the result of the draw provides different effects to a plurality of game players.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective external view of a bingo game machine according to an embodiment in which the present invention is applied to a game machine;

Fig. 2 is a perspective external view of a main structure of a number

- 6 -

drawing apparatus in an embodiment of the present invention;

Fig. 3 is a cross sectional view of a main structure of the number drawing apparatus shown in Fig. 2;

Fig. 4A is a top view of a ball-catching mechanism 4;

Fig. 4B is a view of the underside of a ball-collecting mechanism 5;

Fig. 4C is a top view of the positional relationship between the ball-catching mechanism 4 and the ball-collecting mechanism 5, as they appear during a draw;

Fig. 5 is a block diagram showing a controller 8 in a number drawing apparatus 10;

Fig. 6 is a flowchart illustrating a control process performed by the controller 8 shown in Fig. 5;

Fig. 7 is an illustration of the movement of a ball B at a relatively slow rotational speed of a rotating unit;

Fig. 8 is an illustration of the movement of a ball B at a relatively fast rotational speed of a rotating unit; and

Fig. 9 is an illustration of the movement of a ball B which has rebounded.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment in which the present invention is applied to a bingo game machine is described below with reference to the accompanying drawings.

Fig. 1 is a perspective external view of a bingo game machine. The bingo game machine uses seven resin balls as rolling bodies for the draw

2000 OCT 13 14:59 FAX

- 7 -

of numbers, and provides a plurality of (a maximum of ten) players with a bingo game environment using 25 different symbols. The bingo game machine includes a number drawing apparatus 10 disposed in a playing area so as to be visible by each player, and ten player seats PS. For each player seat PS, a display screen DS is provided to show each player the results of the draw by the number drawing apparatus 10 and to show a record of the draws since the start of the game. Also, a mechanism for providing a game winner (bingo player) with a game prize (token, etc.) is provided. The information displayed on the display screen DS is unique for each player. The number of balls for the draw is not limited to seven, and any number of balls may be used.

Fig. 2 is a perspective external view showing the main structure of the number drawing apparatus 10 in the bingo game machine, and a section of the main structure is shown in Fig. 3.

The number drawing apparatus 10 includes a rotating unit 11 having a surface for rolling balls B, a rotator mechanism 3 for rotating the rotating unit 11, a supply unit 12 for supplying the balls B one by one from the central portion of the rotating unit 11 during rotation to the surface of the rotating unit 11, a ball-supply mechanism 2 for supplying the supply unit 12 with the balls B in sets of seven balls, a ball-catching mechanism 4 provided along the periphery of the rotating unit 11, a ball-collecting mechanism 5 provided on the back of the ball-catching mechanism 4, a display ring 6 provided along the periphery of the ball-catching mechanism 4, and a controller 8 for controlling overall operations of the entire number drawing apparatus.

- 8 -

The display ring 6 is formed to be higher than the ball-collecting mechanism 5, and its inclined sidewall 61 functions as a return wall for returning the ball B to the rotating unit 11. The inclined sidewall 61 has an angle of inclination that can accelerate the ball B when it is being returned.

Although the inclined sidewall 61 illustrated in Fig. 3 is straight, it may be concavely curved.

On the top surface of the display ring 6, 25 indicator units 7 are provided corresponding to 25 different symbols. By emitting light directed at a player who has only to one more number to reach bingo, each indicator unit 7 informs each player of this fact and symbols indicating "BINGO!". Specifically, each indicator unit 7 includes, in a housing, a plurality of light emitters that can emit beams in different directions, and a control mechanism that allows all or some of the light emitters to emit beams based on instructions from the controller 8.

Symbols corresponding to each indicator unit 7 are written so as to be easily seen by each player.

The rotating unit 11 is a light-transmissive disk member, for example, a glass plate or an acrylic plate, and rotates in a fixed plane perpendicular to its vertical axis. The surface of the rotating unit 11 is formed to be plane or is dish-shaped. Preferably, a transparent member is used to form the rotating unit 11, and a photograph or a decorative backing is provided on the back of the rotating unit 11. By doing so, it appears as if the rotating unit 11 does not exist and each ball B is moving autonomously above the backing. This makes the draw entertaining.

- 9 -

The supply unit 12 includes a guide (guidance mechanism) having a supply hole 121 for supplying the ball B carried by the ball-supply mechanism 2 to the surface of the rotating unit 11. This guide is frustum-shaped, in which an outlet surface 122 of the supply hole 121 is an upper base, and an area tangent to the rotating unit 11 is a lower base. The guide accelerates each ball B carried to the outlet surface 122 by an inclined surface 123, and supplies the accelerated ball B to the rotating unit 11. The distance from the supply hole 121 to the surface is set so as to be equal in all directions. This allows the ball B to roll in a random direction under uniform conditions. Although the ball B is carried to the supply hole 12 by, for example, an electric elevating mechanism by the ball-supply mechanism 2, it may be carried by air pressure.

The ball-catching mechanism 4 is a toroidal fixed plate on which 25 catching holes 41 for catching balls B are formed. The ball-collecting mechanism 5 is opposed to the ball-catching mechanism 4 with a predetermined distance therebetween. The ball-collecting mechanism 5 is a toroidal plate having a shape substantially identical to that of the ball-catching mechanism 4, on which 25 collecting holes 51 are formed corresponding to the 25 catching holes 41. The ball-collecting mechanism 5 can be rotated (slid) around a common axis relative to the ball-catching mechanism 4 by a driving mechanism (not shown).

The positional relationship between the ball-catching mechanism 4 and the ball-collecting mechanism 5 is shown in Figs. 4A, 4B, and 4C. Fig. 4A is a top view of the ball-catching mechanism 4, and Fig. 4B is a view of the underside of the ball-collecting mechanism 5. When a draw

- 10 -

begins, ball-catching spaces each having a collecting hole 51 is formed by displacing the ball-collecting mechanism 5 so that all or part of the bottom of each catching hole 41 is covered by the surface of the ball-collecting mechanism 5, as shown in Fig. 4C. Subsequently, until the end of a round of a draw that uses seven balls to select seven different symbols, each ball B is caught in a corresponding ball-catching space. Each ball-catching space may also be referred to as a "pocket".

In order that, in the same round of a draw by the bingo game machine, the same symbol is not selected, it is necessary in one round to avoid a situation in which a plurality of balls B are caught in one pocket. This can be achieved by covering each pocket with a lid, etc. In this embodiment, when the ball B is caught in the pocket, as shown in Fig. 3, the ball B is held so that a part thereof protrudes. This can be achieved by adjusting the gap between the ball-catching mechanism 4 and the ball-collecting mechanism 5. This can easily prevent a plurality of balls B from being caught by the same pocket.

Each catching hole 41 in the ball-catching mechanism 4 is uniquely associated with one of the indicator units 7 on the display ring 6 and one of the symbols. Accordingly, when a ball B is caught in a pocket, the corresponding symbol can be specified.

Each player can know by sight by which of the catching holes 41 each ball B has been caught. However, in order to automatically determine which symbol has been selected, each catching hole 41 is provided with a ball-catch-detecting mechanism such as a microswitch, in this embodiment. When a pocket catches a ball B, the ball-catch-

- 11 -

detecting mechanism sends a catch-detecting signal to the controller 8.

When a round of a draw ends, the catching holes 41 and the collecting holes 51 are set to coincide with each other by moving the ball-collecting mechanism 5, as shown in Fig. 4C, whereby all the balls B simultaneously fall through the pockets. The fallen balls B are collected by a collecting-and-reuse unit (not shown), and each set of seven collected balls B is returned to the ball-supply mechanism 2 again for reuse.

Each of the above-described mechanisms and components are computer-controlled by the controller 8.

Fig. 5 shows the structure of the controller 8. The controller 8 includes a supply-mechanism-control unit 81 for controlling timing for ball supply by the ball-supply mechanism 2, a collecting-mechanism control unit 82 for controlling the ball-collecting mechanism 5, a rotation-control unit 83 for controlling a rotation speed and direction by the rotator mechanism 3, a symbol detector 84 for detecting a symbol, based on a signal output from the ball-catch-detecting mechanism 42 that detects the catching hole 41 in which each ball B is caught, a display control unit 85 for controlling the operation of the corresponding indicator unit 7, and a bingo control unit 86 for association with a bingo function 100.

The rotation-control unit 83 dynamically changes the rotation speed and/or rotational direction by the rotator mechanism 3, thereby changing a value such the rotational speed of the rotating unit 11. This causes each ball B to move randomly.

The bingo function 100 is a mechanism or an electronic component

In step S1003, ball supply is initiated. In other words, the supply-mechanism-control unit 81 controls the ball-supply mechanism 2,

- 13 -

whereby seven balls B are supplied one by one from the supply hole 121 of the supply unit 12 to the surface of the rotating unit 11. In accordance with a friction with the surface of the rotating unit 11, each supplied ball B randomly and autonomously rolls from a supplied position in a direction toward the periphery of the rotating unit 11, and moves outwardly. Any of the catching holes 41 catches the ball B.

In step S1004, the process determines whether any of the catching holes 41 has caught the ball B.

If the process has determined in step S1004 that any of the catching holes 41 has caught the ball B, the symbol detector 84 detects a symbol assigned to the catching hole 41, and notifies the bingo function 100 of the notification result via the bingo control unit 86 in step S1006. The bingo function 100 performs bingo-game processing such as a change of the symbol on the indicator unit 7 for each player's seat.

The above-described steps are repeatedly performed for a round until the process determines in step S1007 that the number of detected balls B is equal to a total of supplied balls B. This enables a bingo game in which results of the draw provide different effects to a plurality of players.

When one round of the draw ends, in step S1008, the bingo control unit 86 instructs the collecting-mechanism-control unit 82 to perform pocket-opening control, namely, control for setting the positions of the catching holes 41 and the collecting holes 51 to mutually coincide by sliding the ball-collecting mechanism 5, whereby seven balls B used in the round fall and are collected.

- 14 -

In step S1009, the process determines whether the bingo function 100 has sent a game-end instruction.

If the process has determined in step S1009 that no game-end instruction has been sent, in other words, when the next round of the draw is performed, the steps after step S1003 are repeatedly performed.

If the process has determined in step S1009 that the bingo function 100 has sent the game-end instruction, the control process is terminated.

As described above, in the number drawing apparatus in this embodiment, the friction between the rotating unit 11 and a ball B causes a centrifugal force to act on the ball B so as to move outwardly, whereby the draw is performed. Movement of the ball B and a time until the ball B is supplied from the supply unit 12 to the rotating unit 11 and is caught in the catching hole 41 slightly change in accordance with the rotational speed of the rotating unit 11.

The time until the ball is supplied and caught is prolonged when the rotational speed of the rotating unit 11 is to some extent fast because the ball B rolls on a complicated path. This case is shown in Fig. 7. The reason that the complicated path is formed is that the ball B is returned by a large rebound of the ball B due to a collision with the sidewall and repulsion by the catching holes 41 because large kinetic energy is given to the ball B by a fast rotational speed of the rotating unit 11.

Conversely, when the rotational speed of the rotating unit 11 is to some extent slow, a time until the ball B is caught in the catching hole 41 shortens as shown in Fig. 8. This is because a rebound of the ball B due to a collision with the sidewall is small, a possibility of a repulsion of the

- 15 -

ball B by the catching holes 41 is low, and the ball B is caught before greatly moving on the rotating unit 11.

A behavior of the ball B greatly differs depending on the weight of the ball B, a friction coefficient of the rotating unit 11, etc. For example, a metal-plated ball and a resin ball differ in behavior even when both balls have the same weight if other conditions are equally set.

Therefore, in an actual operation, the rotational speed of the rotating unit 11 must be changed in view of these characteristics.

When the ball B is not directly caught in one of the catching holes 41, the ball B rebounds (with an acceleration) from the inclined sidewall 61 of the display ring 6 to the rotating unit 11, rolls randomly again, and falls in one of the catching holes 41. Thus, the draw operation cannot be interrupted. Accordingly, management of the time required for one round of the draw is extremely facilitated, which solves the problem of time management for retry of the draw in the foregoing second well-known art.

The scope of the present invention is not limited to the above-described embodiment since the present invention is characterized in that a rolling body such as a ball is controlled to randomly roll on the rotating unit 11 so as to move outwardly, and information specified by the outward movement of the rolling body is used as the draw result.

By way of example, in the above-described embodiment, the supply unit 12 is provided in the central portion of the rotating unit 11. However, the supply unit 12 may be provided at a position excluding the central portion. Also, for supplying the ball B, the ball B may be dropped from a position above the rotating unit 11 without providing the supply unit 12.

- 16 -

Although the above-described embodiment has described the case where a plurality of balls B are supplied one by one to the rotating unit 11 and movement of the ball B is enjoyed by the player, a form in which a plurality of balls B are simultaneously supplied to the rotating unit 11 may be employed.

The above-described embodiment has been described on the assumption that a plurality of balls B have the same quality and the same shape. However, various types of balls may be used for the draw. This allows the balls to differently characteristically move, which can enhance the entertainment in the draw.

Although balls are used as rolling bodies in the above-described embodiment, polygons such as regular dodecahedrons and regular icosahedrons, and things which have an external surface including a plane and which can roll can be used.

Since the draw is possible if each ball B moving outwardly from the rotating unit 11 can be detected, the ball-catching mechanism 4, etc., can be omitted. For example, as in the first well-known art, by assigning unique identifying symbols to rolling bodies, and identifying the identifying symbols in the order the rolling bodies move outwardly from the rotating unit 11, a simplified structure can realize a number drawing apparatus. Also, rolling bodies to which different symbols are assigned in accordance with stop positions or the postures of the rolling bodies, such as dice, are supplied to the rotating unit 11, and the symbols obtained when they move outwardly from the rotating unit 11 may be used as the result of the draw.

- 17 -

WHAT IS CLAIMED IS:

1. A number drawing apparatus, comprising:
a rotating unit having a surface which rolls rolling bodies supplied thereon; and
driving means for rotating said rotating unit in a fixed plane so that the supplied rolling bodies move outwardly from said rotating unit;
wherein information specified by the outward movement of each of the supplied rolling bodies is used as the result of a draw of numbers.
2. A number drawing apparatus according to Claim 1, wherein unique information specified by the moving rolling bodies when the bodies have stopped is used as the result of the draw.
3. A number drawing apparatus according to Claim 2, wherein a plurality of regions to which unique symbols are assigned are provided along the periphery of said rotating unit, and the result of the draw is determined by the symbols assigned to the regions in which the rolling bodies stops.
4. A number drawing apparatus according to Claim 1, wherein N different symbols, determined by the outward movement of N rolling bodies, are specified as the results of the draw, where N represents a natural number not less 2.

00341-5416900

- 18 -

5. A number drawing apparatus, comprising:
- a rotating unit having a surface which rolls rolling bodies supplied thereon;
 - rolling-body-supply means for supplying the rolling bodies from the central portion of said rotating unit to the surface;
 - driving means for rotating said rotating unit in a fixed plane so that each of the supplied rolling bodies randomly travel outwardly from a supplied position in a direction toward the periphery of said rotating unit; and
 - a plurality of catching units provided along the periphery of said rotating unit, the catching units each having a unique symbol assigned thereto;
- wherein the result of a draw of numbers is specified by the symbol assigned to the catching unit in which the moving rolling body is caught.
6. A number drawing apparatus according to Claim 5, wherein the plurality of catching units each include a detecting means for outputting a predetermined signal when the rolling body is caught, and the output signal specifies the symbol assigned to the catching unit in which the rolling body is caught.
7. A number drawing apparatus according to Claim 5, wherein when the catching units catch the rolling bodies, the catching units hold the rolling bodies so that the rolling bodies partly protrude, and allow the rolling bodies to fall with predetermined timing.

00347 3646360

- 19 -

8. A number drawing apparatus according to Claim 5, wherein until N different symbols are determined in sets of N rolling bodies where N represents a natural number not less than 2, the catching units hold the N rolling bodies, and allow all the N rolling bodies to simultaneously fall with predetermined timing.

9. A number drawing apparatus according to Claim 5, wherein the rolling-body-supply means includes a supply hole for supplying the rolling bodies, and a guidance mechanism for accelerating the rolling bodies and for guiding the accelerated rolling bodies to the surface.

10. A number drawing apparatus according to Claim 9, wherein the distance between the supply hole and the surface is equal in all directions.

11. A number drawing apparatus according to Claim 5, further comprising a return wall for returning each of the rolling bodies which has not been caught by any one of the catching units.

12. A number drawing apparatus according to Claim 11, wherein the return wall accelerates the rolling body and returns the accelerated rolling body.

13. A number drawing apparatus according to one of Claims 1 to 12, wherein the rolling bodies are spheres.

- 20 -

14. A number drawing apparatus, comprising:

a rotating unit having a surface which rolls rolling bodies in which each attitude of the rolling bodies or each position at which the rolling bodies stop specifies a unique symbol;

rolling-body-supply means for supplying the rolling bodies from the central portion of the rotating unit to the surface; and

driving means for rotating the rotating unit so that each of the supplied rolling bodies randomly travel outwardly from a supplied position in a direction toward the periphery of the rotating unit;

wherein symbols specified by the moving rolling bodies when the bodies have stopped are used as the results of a draw of numbers.

15. A number drawing apparatus according to one of Claims 1, 5, and 14, wherein the driving means dynamically changes the rotational speed and/or rotational direction of the rolling bodies.

16. A number drawing apparatus according to one of Claims 1 to 12, and 14, wherein the rotating unit consists of a transparent disk member, and rotates in a plane perpendicular to the vertical axis of the disk member.

17. A number drawing apparatus according to Claim 13, wherein the rotating unit consists of a transparent disk member, and rotates in a plane perpendicular to the vertical axis of the disk member.

- 21 -

18. A number drawing apparatus according to Claim 15, wherein the rotating unit consists of a transparent disk member, and rotates in a plane perpendicular to the vertical axis of the disk member.

19. A game machine including a number drawing apparatus and providing a game player with a game prize in accordance with the result of a draw of numbers by the number drawing apparatus,

the number drawing apparatus comprising:

a rotating unit having a surface which rolls rolling bodies supplied thereon; and

driving means for rotating the rotating unit in a fixed plane so that the supplied rolling bodies move outwardly from the rotating unit;

wherein information specified by the outward movement of each of the supplied rolling bodies is used as the result of a draw of numbers.

20. A game machine including a number drawing apparatus and providing a game player with a game prize in accordance with the result of a draw of numbers by the number drawing apparatus,

the number drawing apparatus comprising:

a rotating unit having a surface which rolls rolling bodies supplied thereon;

rolling-body-supply means for supplying the rolling bodies from the central portion of the rotating unit to the surface;

driving means for rotating the rotating unit in a fixed plane so that

- 22 -

each of the supplied rolling bodies randomly travel outwardly from a supplied position in a direction toward the periphery of the rotating unit; and

a plurality of catching units provided along the periphery of the rotating unit, the catching units each having a unique symbol assigned thereto;

wherein the result of a draw of numbers is specified by the symbol assigned to the catching unit in which the moving rolling body is caught.

21. A game machine including a number drawing apparatus and providing a game player with a game prize in accordance with the result of a draw of numbers by the number drawing apparatus,

the number drawing apparatus comprising:

a rotating unit having a surface which rolls rolling bodies in which each attitude of the rolling bodies or each position at which the rolling bodies stop specifies a unique symbol;

rolling-body-supply means for supplying the rolling bodies from the central portion of the rotating unit to the surface; and

driving means for rotating the rotating unit so that each of the supplied rolling bodies randomly travel outwardly from a supplied position in a direction toward the periphery of the rotating unit;

wherein symbols specified by the moving rolling bodies when the bodies have stopped are used as the results of a draw of numbers.

22. A game machine according to one of Claims 19 to 21, wherein

- 23 -

the game machine is a bingo game machine in which the result of the draw provides different effects to a plurality of game players.

- 24 -

ABSTRACT OF THE DISCLOSURE

A number drawing apparatus includes a rotating unit and collecting holes. Each ball, supplied from a supply unit provided in the central portion of the rotating unit when it rotates, randomly rolls on a surface of the rotating unit. A centrifugal force by the rotation causes each ball to move outwardly from the rotating unit, and each ball is caught in one of catching holes. Unique identifying symbols are assigned to the catching holes. This enables the draw.

2000 10/13 FRI 15:04 FAX → BACHMAN • LaPOINTE, PC

FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



Practitioner's Docket No. 00-631**PATENT**

COMBINED DECLARATION AND POWER OF ATTORNEY
(ORIGINAL, DESIGN, NATIONAL STAGE OF PCT, SUPPLEMENTAL, DIVISIONAL,
CONTINUATION, OR C-I-P)

As a below named inventor, I hereby declare that:

TYPE OF DECLARATION

This declaration is of the following type:

(check one applicable item below)

- ☒ original.
☐ design.
☐ supplemental.

NOTE: If the declaration is for an International Application being filed as a divisional, continuation or continuation-in-part application, do not check next item; check appropriate one of last three items.

- ☐ national stage of PCT.

NOTE: If one of the following 3 items apply, then complete and also attach ADDED PAGES FOR DIVISIONAL, CONTINUATION OR C-I-P.

NOTE: See 37 C.F.R. § 1.63(d) (continued prosecution application) for use of a prior nonprovisional application declaration in the continuation or divisional application being filed on behalf of the same or fewer of the inventors named in the prior application.

- ☐ divisional.
☐ continuation.

NOTE: Where an application discloses and claims subject matter not disclosed in the prior application, or a continuation or divisional application names an inventor not named in the prior application, a continuation-in-part application must be filed under 37 C.F.R. § 1.53(b) (application filing requirements — nonprovisional application).

- ☐ continuation-in-part (C-I-P).

INVENTORSHIP IDENTIFICATION

WARNING: If the inventors are each not the inventors of all the claims, an explanation of the facts, including the ownership of all the claims at the time the last claimed invention was made, should be submitted.

My residence, post office address and citizenship are as stated below, next to my name. I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter that is claimed, and for which a patent is sought on the invention entitled:

TITLE OF INVENTIONNUMBER DRAWINGS APPARATUS AND GAME MACHINE THEREWITH

SPECIFICATION IDENTIFICATION

the specification of which:

(complete (a), (b), or (c))

(a) ☒ is attached hereto.

NOTE: "The following combinations of information supplied in an oath or declaration filed on the application filing date with a specification are acceptable as minimums for identifying a specification and compliance with any one of the items below will be accepted as complying with the identification requirement of 37 CFR 1.63:

"(1) name of inventor(s), and reference to an attached specification which is both attached to the oath or declaration at the time of execution and submitted with the oath or declaration on filing;

"(2) name of inventor(s), and attorney docket number which was on the specification as filed; or

"(3) name of inventor(s), and title which was on the specification as filed."

Notice of July 13, 1995 (1177 O.G. 60).

(b) ☐ was filed on _____, as ☐ Serial No. 0 / _____
or ☐ _____
and was amended on _____ (if applicable).

NOTE: Amendments filed after the original papers are deposited with the PTO that contain new matter are not accorded a filing date by being referred to in the declaration. Accordingly, the amendments involved are those filed with the application papers or, in the case of a supplemental declaration, are those amendments claiming matter not encompassed in the original statement of invention or claims. See 37 C.F.R. § 1.67.

NOTE: "The following combinations of information supplied in an oath or declaration filed after the filing date are acceptable as minimums for identifying a specification and compliance with any one of the items below will be accepted as complying with the identification requirement of 37 CFR 1.63:

"(A) application number (consisting of the series code and the serial number, e.g., 08/123,456);

"(B) serial number and filing date;

"(C) attorney docket number which was on the specification as filed;

"(D) title which was on the specification as filed and reference to an attached specification which is both attached to the oath or declaration at the time of execution and submitted with the oath or declaration; or

"(E) title which was on the specification as filed and accompanied by a cover letter accurately identifying the application for which it was intended by either the application number (consisting of the series code and the serial number, e.g., 08/123,456), or serial number and filing date. Absent any statement(s) to the contrary, it will be presumed that the application filed in the PTO is the application which the inventor(s) executed by signing the oath or declaration."

M.P.E.P. § 601.01(a), 7th Ed.

(c) ☐ was described and claimed in PCT International Application No. _____, filed on _____ and as amended under PCT Article 19 on _____ (if any).

(Declaration and Power of Attorney [1-1]—page 2 of 7)

SUPPLEMENTAL DECLARATION (37 C.F.R. § 1.67(b))*(complete the following where a supplemental declaration is being submitted)*

- ☐ I hereby declare that the subject matter of the
- ☐ attached amendment
 - ☐ amendment filed on _____

was part of my/our invention and was invented before the filing date of the original application, above-identified, for such invention.

ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in 37, Code of Federal Regulations, § 1.56,

(also check the following items, if desired)

- ☒ and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable Examiner would consider it important in deciding whether to allow the application to issue as a patent, and
- ☐ in compliance with this duty, there is attached an information disclosure statement, in accordance with 37 C.F.R. § 1.98.

PRIORITY CLAIM (35 U.S.C. §§ 119(a)-(d))

NOTE: "The claim to priority need be in no special form and may be made by the attorney or agent if the foreign application is referred to in the oath or declaration as required by § 1.63. The claim for priority and the certified copy of the foreign application specified in 35 U.S.C. 119(b) must be filed in the case of an interference (§ 1.630), when necessary to overcome the date of a reference relied upon by the examiner, when specifically required by the examiner, and in all other situations, before the patent is granted. If the claim for priority or the certified copy of the foreign application is filed after the date the issue fee is paid, it must be accompanied by a petition requesting entry and by the fee set forth in § 1.17(f). If the certified copy is not in the English language, a translation need not be filed except in the case of interference; or when necessary to overcome the date of a reference relied upon by the examiner; or when specifically required by the examiner, in which event an English language translation must be filed together with a statement that the translation of the certified copy is accurate." 37 C.F.R. § 1.55(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §§ 119(a)-(d) of any foreign application(s) for patent or inventor's certificate or of any PCT International application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

(complete (d) or (e))

- (d) ☐ no such applications have been filed.
- (e) ☒ such applications have been filed as follows.

NOTE: Where item (c) is entered above and the International Application which designated the U.S. itself claimed priority check item (e), enter the details below and make the priority claim.

(Declaration and Power of Attorney [1-1]—page 3 of 7)

**PRIOR FOREIGN/PCT APPLICATION(S) FILED WITHIN 12 MONTHS
(6 MONTHS FOR DESIGN) PRIOR TO THIS APPLICATION
AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. § 119(a)-(d)**

COUNTRY (OR INDICATE IF PCT)	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 37 USC 119
Japan	11-298281	20 October 1999	<input checked="" type="checkbox"/> YES NO <input type="checkbox"/>
			<input type="checkbox"/> YES NO <input type="checkbox"/>
			<input type="checkbox"/> YES NO <input type="checkbox"/>
			<input type="checkbox"/> YES NO <input type="checkbox"/>
			<input type="checkbox"/> YES NO <input type="checkbox"/>

CLAIM FOR BENEFIT OF PRIOR U.S. PROVISIONAL APPLICATION(S)
(34 U.S.C. § 119(e))

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

PROVISIONAL APPLICATION NUMBER

FILING DATE

____ / _____
____ / _____
____ / _____

CLAIM FOR BENEFIT OF EARLIER US/PCT APPLICATION(S)
UNDER 35 U.S.C. § 120

- ☐ The claim for the benefit of any such applications are set forth in the attached ADDED PAGES TO COMBINED DECLARATION AND POWER OF ATTORNEY FOR DIVISIONAL, CONTINUATION OR CONTINUATION-IN-PART (C-I-P) APPLICATION.

(Declaration and Power of Attorney [1-1]—page 4 of 7)

**ALL FOREIGN APPLICATION(S), IF ANY, FILED MORE THAN 12 MONTHS
(6 MONTHS FOR DESIGN) PRIOR TO THIS U.S. APPLICATION**

NOTE: If the application filed more than 12 months from the filing date of this application is a PCT filing forming the basis for this application entering the United States as (1) the national stage, or (2) a continuation, divisional, or continuation-in-part, then also complete **ADDED PAGES TO COMBINED DECLARATION AND POWER OF ATTORNEY FOR DIVISIONAL, CONTINUATION OR C-I-P APPLICATION** for benefit of the prior U.S. or PCT application(s) under 35 U.S.C. § 120.

POWER OF ATTORNEY

I hereby appoint the following practitioner(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

(list name and registration number)

Robert H. Bachman (19,374), Gregory P. LaPointe (28,395),
Barry L. Kelmachter (29,999), and George A. Coury (34,309),
all of Bachman & LaPointe, P.C., 900 Chapel Street, Suite
1201, New Haven, CT 06510-2802

(check the following item, if applicable)

- ☒ I hereby appoint the practitioner(s) associated with the Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.
- ☐ Attached, as part of this declaration and power of attorney, is the authorization of the above-named practitioner(s) to accept and follow instructions from my representative(s).

SEND CORRESPONDENCE TO**DIRECT TELEPHONE CALLS TO:**
(Name and telephone number)

☒ Address
Bachman & LaPointe, P.C.
900 Chapel Street, Suite 1201
New Haven, CT 06510-2802

Gregory P. LaPointe
(203) 777-6628

☐ Customer Number _____

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

NOTE: Carefully indicate the family (or last) name, as it should appear on the filing receipt and all other documents.

NOTE: Each inventor must be identified by full name, including the family name, and at least one given name without abbreviation together with any other given name or initial, and by his/her residence, post office address and country of citizenship. 37 CFR § 1.63(a)(3).

NOTE: Inventors may execute separate declarations/oaths provided each declaration/oath sets forth all the inventors. Section 1.63(a)(3) requires that a declaration/oath, *inter alia*, identify each inventor and prohibits the execution of separate declarations/oaths which each sets forth only the name of the executing inventor. 62 Fed. Reg. 53,131, 53,142, October 10, 1997.

Full name of sole or first inventor

Takashi Yamaguchi
(GIVEN NAME) (MIDDLE INITIAL OR NAME) FAMILY (OR LAST NAME)

Inventor's signature _____

Date _____ Country of Citizenship JAPAN

Residence _____

Post Office Address _____

Full name of second joint inventor, if any

Takashi Kumabe
(GIVEN NAME) (MIDDLE INITIAL OR NAME) FAMILY (OR LAST NAME)

Inventor's signature _____

Date _____ Country of Citizenship JAPAN

Residence _____

Post Office Address _____

Full name of third joint inventor, if any

Takashi Uchiyama
(GIVEN NAME) (MIDDLE INITIAL OR NAME) FAMILY (OR LAST NAME)

Inventor's signature _____

Date _____ Country of Citizenship JAPAN

Residence _____

Post Office Address _____

(Declaration and Power of Attorney [1-1]—page 6 of 7)

(check proper box(es) for any of the following added page(s)
that form a part of this declaration)

- ☐ **Signature** for fourth and subsequent joint inventors. Number of pages added _____

* * *

- ☐ **Signature** by administrator(trix), executor(trix) or legal representative for deceased or incapacitated inventor. Number of pages added _____

* * *

- ☐ **Signature** for inventor who refuses to sign or cannot be reached by person authorized under 37 CFR 1.47. Number of pages added _____

* * *

- ☐ Added page for **signature** by one joint inventor on behalf of deceased inventor(s) where legal representative cannot be appointed in time. (37 CFR 1.47)

* * *

- ☐ Added pages to combined declaration and power of attorney for divisional, continuation, or continuation-in-part (C-I-P) application.

☐ Number of pages added _____

* * *

- ☐ Authorization of practitioner(s) to accept and follow instructions from representative.

* * *

(if no further pages form a part of this Declaration,
then end this Declaration with this page and check the following item)

☒ This declaration ends with this page.